

OVERBAND MAGNETIC SEPARATORS DND-AC



SOLLAU self-cleaning overband magnets are fitted with permanent (ferrite or neodymium) magnets.

Our separators are unique in their **high efficiency** - they can be suspended up to 500 mm above the conveyor and can capture contaminants from 0.5 mm in size!

In the production, we focus on quality i. e. **all-stainless steel design** and its compactness with no blind spots between the magnetic core and the sidewall.



Our provided warranty on self-cleaning overband magnets is 10 years!

WARRANTY

10-year

SUSPENSION HEIGHT

up to 500 mm

RESISTANCE

all-stainless design

SOLUTION TO-MEASURE

12 model series

SEPARATOR EFFICIENCY

- Hanging height up to 500 mm
- Separation of magnetic particles from 0,5 mm

TECHNOLOGICAL INNOVATIONS

- All-stainless steel design - high durability and long working life
- No blind spots between the magnetic core and the sidewall
- Weight from 440 kg
- Separator with a magnetic induction of 1,010 G (measured at a distance of 200 mm from the separator belt)

PRODUCTION

- Custom production
- 12 model series = the most suitable solution for your application

SERVICE

- Guaranteed service intervention within 2 working days

HOW WILL WE TAKE CARE OF YOU?



1. We will come



2. We will focus and design




3. We make to-measure



4. We will install



5. We will put into operation and train



6. We will provide authorized service

SOLLAU S.R.O.

Hrivinuv Ujezd 212 | 763 07 Velky Orechov | Czech Republic
Phone.: +420 576 013 873 | E-mail: info@sollau.cz
Ino.: 29261759 | Tax Ino: CZ29261759

WWW.SOLLAU.COM